

Product Datasheet

EXP-AH-5GS Outdoor Heated Emergency Safety Shower



Trace tape heated and pre-insulated floor mounted drench shower intended for use where there is a possibility of the water inside the shower freezing due to extreme cold climates. Suitable for both hazardous and non-hazardous areas.

Specifications

MATERIALS OF CONSTRUCTION

PIPEWORK AND FITTINGS	316L stainless steel with 150lb medium wall tubulars and fittings
OPERATING VALVE	316L stainless steel, two piece stay open valve
SHOWER SPRAY OUTLET	Machine moulded nylon 6 red shower nozzle
INSULATION & OUTER CASING	Polyurethane foam insulation with a medium density polyethylene impact resistant outer casing
STANDARD FINISH	White with green/white safety stripes (alternative colours available)

SERVICES

WATER INLET	1 1/4" Male BSP
DESIGN OPERATING PRESSURE	1.5 to 6 BAR G (22 to 87 PSI) (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
HEATING TYPE	Trace tape heated and pre-insulated
HEATING LOAD	42 Watts
ELECTRICAL EQUIPMENT - Non-hazardous	Suitable for use in areas classified as non-hazardous
ELECTRICAL EQUIPMENT - Hazardous	ATEX zones 1 and 2. Gas group IIC, temp class T5/T6. Dust group IIIC and temp class T85/100
ELECTRIC SUPPLY	230V Single Phase, 50/60Hz or 110V avail
MINIMUM FLOW AT OPERATING PRESSURE	Shower: 76 litres/minute minimum (20 US Gallons)

ENVIRONMENTAL OPERATING TEMPERATURE

MINIMUM AMBIENT OPERATING TEMPERATURE	-20° C (-4° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	38° C (100.4° F)

OPERATIONAL

SHOWER SPRAY OPERATION	Pull handle (optional foot panel for hands free operation)
------------------------	--

WEIGHTS and DIMENSIONS

DIMENSIONS - STANDARD ORIENTATION (WxDxH)	210mm (8.3in) x 890mm (35in) x 2330mm (91.7in)
WEIGHT (NO OPTIONS)	21kg (46lb)

View our Guide to the ANSI/ISEA Z358.1-2014 International Standard for Emergency Eyewash and Shower Equipment at www.hughes-safety.com



HUGHES




HUGHES-SAFETY.COM

Justrite Safety Group


www.hughes-safety.com

EXP-AH-5GS

Outdoor Heated Emergency Safety Shower



FIXING DETAIL VIEW



HUGHES



HUGHES-SAFETY.COM

Justrite Safety Group

Hughes Safety Showers Ltd, Whitefield Road, Bredbury, Stockport SK6 2SS UK.

Email: sales@hughes-safety.com

Tel: +44 (0)161 430 6618

Registered No. 0939240. VAT Registration No. 918 5005 32. Hughes Safety Showers Ltd is a Justrite Group Company.