

# Product Datasheet

## Mobile self-contained heated safety shower with eye wash - 1200L

### STD-MH-P-1200L

It is essential to provide emergency safety showers for use by employees at risk of exposure to hazardous substances, whatever the location. This immersion heated 1200 litre mobile safety shower with closed bowl eye/face wash unit allows flexibility of location, being easily transported behind a suitable vehicle using the towing hitch provided.

Designed to meet EN and ANSI standards, it is capable of delivering a continuous flow of tepid water for over 15 minutes at a rate of 76 litres per minute. The optional insulated jacket is advised for use during colder months to prevent freezing and maintain the water temperature within the tepid range.



## Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
TANK	Polyethylene
CHASSIS	Galvanised mild steel
AXLE/SUSPENSION	Avonride rubber torsion beam axle fitted with 200x50 auto reverse brakes
COUPLING	Avonride auto reverse coupling fitted with 40mm eye, break away cable and parking brake lever
ANCILLARY EQUIPMENT	Moulded mud guards, front telescopic jockey wheel, lighting board, rear propstand options
SHOWER NOZZLE	Machine moulded nylon 6
EYE WASH	ASA
SERVICES	
CAPACITY	1200 L / 317 US gal
ELECTRICAL SUPPLY: FLAMEPROOF	Stainless steel pump rating: 0.9kW, 230V Immersion heater: 3kW, 230V Trace tape connection: 20W (if fitted)
ELECTRICAL SUPPLY: NON-FLAMEPROOF	Pump rating: 0.4kW, 230V Immersion heater: 3kW, 230V (or 1.7kW, 110V) Trace tape connection: 20W (if fitted)
WATER INLET	18" hinged manlid cover
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	0C / 32F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Push down lever
EYE WASH	Pull lid down

# General Arrangement Drawing

## Mobile self-contained heated safety shower with eye wash - 1200L

STD-MH-P-1200L

### DIMENSIONS & WEIGHT

DIMENSIONS (WxDxH)

Assembled: 1530mm (60.2in) x 3556mm (140in) x 2770mm (109.1in)

WEIGHT

Empty: 260kg (573lb) Full: 1460kg (3219lb)

