

## Trace tape heated and insulated PPE decontamination shower with multiple nozzles

DEC-DH-29D  
DEC-DH-29DS

In outdoor locations subject to the chance of freezing weather conditions, this trace tape heated and insulated PPE decontamination shower is essential. Ten spray nozzles provide a top to toe wash down and the self-draining valve ensures water leaves the pipework after use to prevent stagnation. An optional drain sump can be added to help contain the excess contaminated water.



## Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel (DS) or galvanised mild steel (D)
OPERATING VALVE	Stainless steel, full bore, stay open ball valve
SHOWER SPRAY OUTLET	UPVC
PANELLING	Green heavy duty GRP
SERVICES	
WATER INLET	1 1/4" Female BSP
DESIGN OPERATING PRESSURE	4 to 6 BAR G / 57 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	250 L per minute / 66 US gal per minute
ELECTRICAL SUPPLY	230V, single phase, 50/60Hz (110V optional)
AMBIENT OPERATING TEMPERATURE	
MINIMUM	-10C / 14F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Push down lever
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	1170mm (46in) x 1095mm (43in) x 2315mm (91in)
WEIGHT	160kg / 353lb

# General Arrangement Drawing

## Trace tape heated and insulated PPE decontamination shower with multiple nozzles

DEC-DH-29D

DEC-DH-29DS

