

Product Datasheet

Trace tape heated pedestal mounted eye wash with ASA closed bowl and integral handheld shower

STD-H-25KS/P

Suitable for outdoor use where there is the possibility of water within the pipework freezing. Both hazardous and non-hazardous areas can benefit from the trace tape heating and polyurethane foam insulation to provide frost protection. The eye/face wash unit has a flow rate of 12 litres per minute and is complemented by an integral handheld eyebath diffuser on a flexible hose to decontaminate the affected area directly.

Meets EN15154 and ANSI Z358.1-2014 standards.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK	Stainless steel
BOWL/LID	ASA
DIFFUSERS	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
INSULATION & OUTER CASING	Polyurethane foam insulation with a medium density polyethylene impact resistant outer casing
STANDARD FINISH	White with green/white safety stripes
SERVICES	
WATER INLET	1 1/4" Male BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Eye wash: 12 L per minute / 3 US gal per minute Handheld: 1.5 L per minute / 0.4 US gal per minute
HEATING TYPE	Trace tape heated
HEATING LOAD	21 Watts
ELECTRICAL EQUIPMENT	ATEX Zone 1 & 2 gas groups IIA and IIB, Temp Class T3 (IIC available)
ELECTRIC SUPPLY	240V Single Phase, 50/60Hz or 110V available
AMBIENT OPERATING TEMPERATURE	
MINIMUM	-25C / 31F
MAXIMUM	35C / 95F
OPERATION	
EYE/FACE WASH	Lift lid
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	475mm (18.7in) x 723mm (28.5in) x 1113mm (43.8in)
WEIGHT	20kg / 44lb

General Arrangement Drawing

Trace tape heated pedestal mounted eye wash with ASA closed bowl and integral handheld shower

STD-H-25KS/P

