

Product Datasheet

Portable self-contained gravity fed eye wash - 60 L / 16 US gal

STD-68G

Where a fixed eye/face wash installation is not possible, this portable gravity fed unit can be table mounted or wall mounted. The 60 L / 16 US gal capacity eye wash station delivers 3 L / 0.8 US gal per minute of potable water for 15 minutes, conforming to EN15154 and ANSI Z358.1-2014 standards.

Suitable for indoor use, and with the addition of the optional heated cabinet can also be installed outdoors.



Specifications

MATERIALS OF CONSTRUCTION	
BODY & DELIVERY MANIFOLD	High density polyethylene
SPRAY HEADS	Engineering grade thermoplastic
TUBING TO MANIFOLD	High density polyethylene
STANDARD FINISH	Green and yellow
SERVICES	
CAPACITY	60 L / 16 US gal
FLOW RATES	3 L per minute / 0.8 US gal per minute
TUBING SIZE	9.5mm / 0.37in
OPERATION	
EYE/FACE WASH	Pull down manifold
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	513mm (20.2in) x 540mm (21.3in) x 457mm (18in)
WEIGHT	Empty: 8.2kg / 18lb. Full: 68kg / 151lb

General Arrangement Drawing

Portable self-contained gravity fed eye wash - 60 L / 16 US gal STD-68G

