Product Datasheet

Ring main laboratory safety shower with eye wash

LAB-23GS

This emergency safety shower connects directly to the water ring main pipework in the laboratory for the perfect space saving option. The durable powder coated stainless steel pipework is resistant to corrosion and easy to clean. Designed to meet the requirements of the European Standard EN15154 for Laboratories and ANSI Z358.1-2014.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
OPERATING VALVE	Stainless steel
SHOWER ROSE	Powder coated stainless steel
STANDARD FINISH	Green powder coated polyester
SERVICES	
WATER INLET	1" female BSP
OPERATING PRESSURE	2 to 6 BAR G $\!\!\!/$ 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	260mm (10.2in) x 600mm (23.6in) x 230mm (9.1in)
WEIGHT	5kg (11lb)



General Arrangement Drawing

Ring main mounted laboratory safety shower

LAB-23GS



