## Ceiling mounted laboratory safety shower

## LAB-23GS/V

For laboratory environments in both a professional and school setting, this ceiling mounted unit is ideal where space is limited. The powder coated stainless steel pipework ensures resistance to corrosive and flammable materials. For a rapid response to an accidental spill or splash the easy-grip pull rod allows for instant activation. Designed to meet the requirements of the European Standard EN15154 for Laboratories and ANSI Z358.1-2014.



## Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
OPERATING VALVE	Stainless steel
SHOWER ROSE	Powder coated stainless steel
STANDARD FINISH	Green powder coated polyester
SERVICES	
WATER INLET	1" male BSP
OPERATING PRESSURE	$2\ to\ 6\ BAR\ G\ /\ 29\ to\ 87\ PSI$ (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	76 L per minute / 20 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	300mm (11.8in) x 260mm (10.2in) x 312mm (12.3in)
WEIGHT	5kg (11lb)



## Ceiling mounted laboratory safety shower

LAB-23GS/V





