

# Product Datasheet

## Unheated safety shower with eye wash and handheld eyebath

STD-18KS/25K

For those at risk of injury from accidental chemical spills in the workplace, this combination safety shower and eye/face wash offers an EN15154 and ANSI Z358.1-2014 compliant solution. The floor mounted shower is ideal for indoor use and features a closed bowl eye wash unit incorporating an auxiliary handheld eye bath on a flexible hose. Activation is simple and can be made hands-free with the addition of an optional foot treadle.

Supplied with safety shower and eye/face wash sign including inserts for mounting to the pipework or pull handle.



## Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
OPERATING VALVE	Stainless-steel, two-piece stay open valve
SHOWER NOZZLE	Injection moulded nylon 6
EYE WASH	Acrylic capped ASA
EYE WASH DIFFUSERS	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
STANDARD FINISH	Polished brush
SERVICES	
WATER INLET	1¼" female BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye wash: 12 L per minute / 3 US gal per minute Handheld eye bath: 8 L per minute / 2 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
EYE WASH	Pull lid down
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	483mm (19in) x 716mm (28.1in) x 2320mm (91.3in)
WEIGHT	25kg (55lb)

# General Arrangement Drawing

## Unheated safety shower with eye wash and handheld eyebath

STD-18KS/25K

