

# Product Datasheet

## Pedestal mounted powder coated stainless steel eye wash

L85GSP

Laboratories, schools and store rooms can all benefit from the corrosion resistant properties of this powder coated stainless steel eye wash mounted on a pedestal. Place within 15 meters of a hazard for immediate relief in the event of a chemical splash or spill. A 3 US gallon per minute flow rate and fine mesh strainers ensure an optimal washing action is achieved. Simple to activate in an emergency using the push plate. Meets the requirements of ANSI Z358.1-2014.



## Specifications

MATERIALS OF CONSTRUCTION	
BOWL/LID	Powder coated stainless steel
DIFFUSERS	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
PIPEWORK	Stainless steel
STANDARD FINISH	Green powder coated polyester finish
SERVICES	
WATER INLET	1" Male NPT
OPERATING PRESSURE	2.0 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
EYE/FACE WASH	Push plate (optional foot treadle control for hands free operation)
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	429mm (16.9in) x 547mm (21.5in) x 1110mm (43.7in)
WEIGHT	8kg / 18lb

# General Arrangement Drawing

## Pedestal mounted powder coated stainless steel eye wash

L85GSP

