

# Product Datasheet

## Wall mounted laboratory safety shower with eye wash

### L33GS34G

Laboratory floor space can often be limited, choose this wall mounted safety shower with an open bowl eye wash to ensure employees have access to a reliable decontamination solution. The powder coated stainless steel pipework and eye/face wash bowl ensures resistance to corrosive and flammable materials whilst being easy to clean. Designed to meet the requirements of ANSI Z358.1-2014.



## Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
OPERATING VALVE	Stainless steel, full bore, stay open ball valve
SHOWER ROSE	Powder coated stainless steel
EYE WASH BOWL	Powder coated stainless steel
EYE WASH DIFFUSER	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
STANDARD FINISH	Green powder coated polyester
SERVICES	
WATER INLET	1" male NPT
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
EYE WASH	Push plate
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	320mm (12.6in) x 815mm (32.1in) x 1410mm (55.5in)
WEIGHT	13kg (29lb)

# General Arrangement Drawing

## Wall mounted laboratory safety shower with eye wash

L33GS34G

