

Product Datasheet

2000L Tank fed safety shower - immersion heated MH14KS2000

Featuring a self-contained tank there is no need for a mains water supply making this the best solution for remote locations. Meets and exceeds ANSI standards by providing tepid water for over 15 minutes to the shower and eye/face Wash.

The integral immersion heater and thick polyurethane insulation maintain a safe water temperature within the overhead tank in cold ambient climates.

Features internally mounted, covered eye/face wash unit and rectangular hollow section stainless steel frames designed and built to be earthquake-proof, conforming to the California Building Code.



Shown with optional GRP panels, eye wash foot treadle and shower foot activation

Specifications

MATERIALS OF CONSTRUCTION	
FRAME AND LEGS	Stainless steel
WATER TANK	2000 L (528 US gal) capacity medium density polyethylene MDPE
TANK SURROUND AND LID	GRP
INSULATION	40mm (1½") foil backed polyurethane
PIPING AND VALVE	uPVC and stainless steel*
SHOWER CONTROL VALVE	uPVC 1½" ball valve*
EYE WASH CONTROL VALVE	½" stainless steel full flow ball valve
EYE WASH STRAINER	½" stainless steel*
BALLCOCK VALVE	2 x ½" brass*
OVERFLOW	1" female uPVC*
SHOWER ROSE	GRP, stainless steel
PANIC BAR	Red powder coated stainless steel
FOOT CONTROL OPTIONS	Foot panel (for shower) and powder coated stainless steel treadle (for eye wash)
FASTENERS AND FIXINGS	Stainless steel
SERVICES	
ELECTRICAL EQUIPMENT	General purpose or CLASS 1, DIV 2, GRPS C&D
ELECTRICAL SUPPLY	110V, single phase, 50/60Hz, 1.7kW (220V optional)
IMMERSION HEATER RATING	1.7kW (2.5kW for 220V)
WATER INLET	¾" female NPT
OPERATING PRESSURE	0.5 to 7 BAR G / 7 to 101 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye/face wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	-30C / -22F (with the addition of trace tape heating to the valve assembly and eye wash feed line)
MAXIMUM	35C / 95F

** all stainless steel piping and valves available as an option*

Specifications continued overleaf

General Arrangement Drawing

2000L Tank fed safety shower - immersion heated

MH14KS2000

Specifications cont.

OPERATION	
SHOWER	Push activated panic bar (or optional foot panel)
EYE WASH	Lift lid (or optional foot panel)
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	2057mm (81in) x 1498mm (59in) x 3759mm (148in)
WEIGHT	Empty: 482kg (1062lb). Full: 2482kg (5472lb)

