

Product Datasheet

Portable decontamination shower with foldaway frame, side sheeting and sump

PORTA1000

PORTA1000G (no side sheeting or sump)

Ideal for the decontamination of personal protective clothing or as a temporary emergency safety shower that can be deployed in just five minutes. This portable solution comprises a robust aluminum collapsible frame with integral roof canopy, side panelling and sump to contain contaminated water. Once connected to a water supply the overhead shower and lower body jets are simple to activate using the pull handle.



Specifications

MATERIALS OF CONSTRUCTION	
FRAME	Aluminum
ROOF CANOPY & SIDE SHEETING	Heavy duty PVC coated nylon
SUMP & FOOT GRATING	GRP
NOZZLES	PVC and injection moulded nylon 6
HOSE	Yellow PVC, cover soft PVC, reinforcement polyester yarn
SERVICES	
SUPPLY PRESSURE	2 to 5 BAR G / 29 to 72 PSI
WATER INLET	22mm (1") geka fitting
WATER DRAIN OUTLET	38mm (1½") cam lock fitting
COLLECTION SUMP CAPACITY	150 L / 40 gal
OPERATION	
SHOWER	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	Assembled: 1060mm (41.7in) x 1060mm (41.7in) x 2710mm (106.7in) Packed: 500mm (19.7in) x 1700mm (66.9in) x 300mm (11.8in)
WEIGHT	35kg (77lb)

General Arrangement Drawing

Portable decontamination shower with foldaway frame, side sheeting and sump

PORTA1000

PORTA1000G (no side sheeting or sump)

