

Product Datasheet

Wall mounted PPE decontamination shower with detergent inducer and hose brush

DECV2

Where space is at a premium, this wall mounted PPE decontamination shower is an excellent choice. Incorporating a detergent inducing venturi, feeding an overhead shower and brush on a flexible hose, it provides an effective full body, first stage cleaning process. Four shower nozzles help to complete the secondary wash down.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
OPERATING VALVE	Stainless steel, full bore, stay open ball valve
SHOWER ROSE	Stainless steel
SHOWER SPRAY OUTLET	UPVC
SERVICES	
WATER INLET	3/4" Female NPT
DESIGN OPERATING PRESSURE	2.8 to 6 BAR G / 40 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	60 L per minute / 16 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Push down lever
HOSE BRUSH	Push down lever
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	890mm (35in) x 900mm (35.4in) x 1475mm (58.1in)
WEIGHT	29kg / 63.9lb

General Arrangement Drawing

Wall mounted PPE decontamination shower with detergent inducer and hose brush DECV2

