

Product Datasheet

Self-draining pedestal mounted eye wash with ABS open bowl

SD75GP

SD75GSP

Intended for use in hot climates. The innovative design of this pedestal mounted eye wash allows standing water, potentially subject to solar radiation, to drain away from the standpipe and avoid scalding a casualty upon initial activation. This ABS plastic open bowl eye/face wash in high visibility yellow is simple to operate using the push plate. An optional treadle can be added to enable hands-free foot activation.

Meets ANSI Z358.1-2014 standards.



Specifications

| MATERIALS OF CONSTRUCTION | |
|-------------------------------|--|
| BOWL/LID | ABS |
| DIFFUSERS | Chrome plated brass retaining ring, stainless steel filter mesh, plastic body |
| PIPEWORK | Stainless steel (GS) or galvanised mild steel (G) |
| SERVICES | |
| WATER INLET | 1 1/4" Female BSP |
| OPERATING PRESSURE | 2.0 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve) |
| MINIMUM FLOW RATES | 12 L per minute / 3 US gal per minute |
| AMBIENT OPERATING TEMPERATURE | |
| MINIMUM | 5C / 41F |
| MAXIMUM | 55C / 131F |
| OPERATION | |
| EYE/FACE WASH | Push down lever (optional foot treadle control for hands free operation) |
| DIMENSIONS & WEIGHT | |
| DIMENSIONS (WxDxH) | 429mm (16.9in) x 443mm (17.4in) x 1273mm (50.1in) |
| WEIGHT | 10kg / 22lb |

General Arrangement Drawing

Pedestal mounted eye wash with ABS open bowl

SD75GP
SD75GSP

